



May 5, 2020

File Ref: C19-5621/A

Fraser Valley Regional District
45950 Cheam Avenue
Chilliwack, BC V2P 1N6

Attention: David Bennett, Planner

Reference: 52964 Yale Rd., Rosedale, B.C
Drainage Design Brief

Summary

The following outlines the proposed storm water management plan for the commercial development proposed at 52964 Yale Road. The existing development south of the proposed development constructed a storm sewer system that provided service to the subject lot. This included storm sewer, storm water treatment systems, and infiltration facilities.

1. Existing Development

The existing development south of the proposed development was designed by MJL Engineering Ltd., Project No. 212012, dated October 12, 2012. The design was for a proposed gas station, roadway design, and future development for five different buildings. The design included water, sanitary, and storm services provided for each location, and labeled future if it was to be built at a later time. The proposed storm system at the time of development included storm sewers, catch basins, storm water treatment, and infiltration facilities.

2. Water treatment

An oil/silt treatment facility is located on the development south of the project site and just before the infiltration facility. This treatment facility appears to have been designed to treat all of the run-off entering the infiltration facility.

3. Detention/Infiltration Design

The existing design from MJL Engineering's design proposed an infiltration rock pit. The rock pit was designed to include the proposed development, as well as other areas, at a runoff coefficient of 0.90. This information can be seen on the attached sheet SK01. Calculating the pervious and impervious area of the new commercial development, the weighted average run-off coefficient is as follows:

Pervious area (R=0.30):	369 sq. m
Impervious area (R=0.90):	3501 sq. m
Total area:	3870 sq. m
Weighted Run-off Coefficient:	$(369 \times 0.30) + (3501 \times 0.90) / 3870 = 0.84$

The required infiltration system storage volume that is required for the proposed development, including the catchment areas originally planned for the existing infiltration system, is 219 m³. Refer to the attached spreadsheets for calculations.

The infiltration storage volume provided by the existing infiltration system is 221 m³. Therefore, there is adequate capacity in the existing infiltration system to handle the storm water run-off for the proposed development.

4. Signature

We trust that this information meets your expectations. Should you have any questions or concerns, please contact the undersigned at your convenience.

Yours truly,
Wedler Engineering LLP

Per:

Reviewed by:



Patrick Mango
Civil Design Engineer

André Gagné, P. Eng.
Project Engineer
agagne@wedler.com

cc: Steven Cross, X Architecture
Jay Lee, Rhee Ga Holdings

Enclosures:

- Wedler Drawing No. C19-5621/A-SK01: Storm Water Management Plan – Overall Design
- Wedler Engineering Soak-Away Sizing Calculation Sheet




INFORMATION SHOWN IS FROM
DWGS CREATED BY MJL
ENGINEERING LTD. PROJECT NO.
212012 DATED OCTOBER 12, 2012

STORMWATER DETENTION

	LOT 1, SL 1 SL 2	SL 3	SL 4
AREA (Ha.)	1.603	0.55	0.88
COEFFICIENT	0.90	0.90	0.90
VOID RATIO (50mm CLEAR-%)	40	40	40
VOLUME H ₂ O TO BE RETAINED (cu.m.)	221	76	122
REQUIRED ROCK PIT AREA (cu.m.)	554	190	304

BASED ON THE INFORMATION
PROVIDED FROM DRAWINGS FROM
MJL ENGINEERING:
PROPOSED WEIGHTED AVERAGE
RUNOFF COEFFICIENT LOT 1: 0.84
BASED ON THE BUILT DESIGN, THE
SOAK AWAY IS DESIGNED TO HANDLE
PROPOSED RUNOFF FROM LOT 1.



K:\56005699\C19-5621a - Comm 52964 Yale Rd Rosedale\Design\Current Drawing Files\C19-5621A-Sheets.dwg 2020/05/05 11:17:51 AM p.mango

LEGAL:	A	ISSUED FOR DEVELOPMENT PERMIT	2020-05-01	PJM					
REV		DESCRIPTION	YYYY-MM-DD	BY	REV	DESCRIPTION	YYYY-MM-DD	BY	

PROJ. MGR.	ALG
DESIGN/DRAWN	PJM
PEER REVIEWED	--
HORIZ. SCALE	1:400
VERT. SCALE	

THE WEDLER GROUP

- Abbotsford 1,604,746.0300
- Chilliwack 1,604,792.0651
- Courtenay 1,250,334.3263
- Surrey 1,604,588.1919

WEDLER ENGINEERING

www.wedler.com

RHEE GA 0808 HOLDINGS LTD.
COMMERCIAL DEVELOPMENT
52964 YALE ROAD, ROSEDALE, BC

**STORM WATER MANAGEMENT PLAN
OVERALL DESIGN**

DRAWING NO.	OF 1
C19-5621/A-SK01	
LOCAL GOVERNMENT FILE	
PHASE	REVISION
	A



SOAK-AWAY SIZING CALCULATION SHEET

Client: Rhee Ga Holdings
 Project: 52964 Yale Rd. Commercial Development
 Project #: C19-5621/A
 Soak-Away Desc: Existing Soak Away - Updated Design

Date Printed: May 5, 2020
 By: PJM

	Area (m ²)	Runoff Coefficient
Lot 1 (Proposed)	3870	0.84
Ex. SL1	3917	0.9
Fut. SL2	8248	0.9
Combined	16035	0.89

Infiltration Rate Used	144	mm/hr
Length	37.00	m
Width	15.00	m
Depth	1.00	m
Footprint	555	m ²
Perf. Pipe Size	150	mm
Perf Pipe Storage	0.7	m ³
Storage Provided (40% void ratio)	222.4	m ³
Max. Storage Req'd	219.6	m ³

Discharge Data

Allowable Offsite Release 0.0000 m³/s **None**
 Release rate from infiltration 0.0222 m³/s

Time min	Intensity mm/hr	Q _{in} m ³ /s	Q _{out} m ³ /s	Vol.in m ³	Vol.out m ³	Vin-Vout m ³
0	0.00	0.0000	0.0000	0.00	0.00	0.00
5	64.16	0.2533	0.0222	75.98	6.66	69.32
10	45.56	0.1798	0.0222	107.90	13.32	94.58
15	37.29	0.1472	0.0222	132.47	19.98	112.49
30	26.48	0.1045	0.0222	188.13	39.96	148.17
60	18.80	0.0742	0.0222	267.16	79.92	187.24
120	13.35	0.0527	0.0222	379.40	159.84	219.56
360	7.76	0.0306	0.0222	661.48	479.52	181.96
720	5.51	0.0217	0.0222	939.37	959.04	-19.67
1440	3.91	0.0154	0.0222	1334.01	1918.08	-584.07